Wichard, 1 ZI de Felet, CS 50085, 63307 Thiers, France
Tél: +33 (0)4 73 51 65 00 — E-mail: marine@wichard.com

Babystay adjuster with ratchet - For 7/8/9 wire - Dia 14 mm

Part #5587



Description

Ideal for fitting a removable inner forestay (genoa or solent)
Easy to install thanks to the snap shackle
Robust and performant
Strongly recommended when there is a furling system
The ratchet model offers great comfort and ease of use during operations.
Technical data:
Handling load: 2500 Kg
Length pin to pin closed / open: 360 / 520 mm
Toggle length x width: 17 x 22 mm
Pin diameter: 14 mm
Stud diameter: 14 mm
For wire diameter: 7 / 8 / 9 mm

Applications

installation of a babystay adjuster to set up a solent, genoa ....
Improve the overall performance of the boat (especially those equipped with a reefing-furling system)

Technical information

Materials	Snap hook in HR 17.4 PH stainless steel 316L stainless steel grade
Working load (kg)	3200
Breaking load (kg)	6700
Weight (kg)	1.856

Caption

Working load (WL) : for nautical applications

Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard strives to ensure, to the best of its ability, the accuracy and the update of the information disseminated on this document, and reserves the right to correct at any time and without notice the content, as well as to evolve its products.

In the case of an industrial application, please contact our sales and technical department to validate the use of these products. The request for certificates can be made directly with the sales department when ordering the products.

Non-contractual pictures.

© Wichard 2020-2026